

Specifications Blue Torch II Series

Pos	Torch type	Max. rated current(DC)	rating	wire diameter	Cable lenght	weight	Handle type	Cooling system	remark
1	WT230-SED	230 A	60%	(1.0) / 1.2	3.0 mtr.	2,3 kg	small	aircooled	
2	WT230-MED	230 A	60%	(1.0) / 1.2	4.5 mtr	3,0 kg	ergo	aircooled	
3	WT280-SED	280 A	60%	(1.0) / 1.2	3.0 mtr.	2,7 kg	ergo	aircooled	
4	WT280-MED	280 A	60%	(1.0) / 1.2	4.5 mtr	3,6 kg	ergo	aircooled	
5	WT330-SED	330 A	60%	1.2 / (1.6)	3.0 mtr.	3,0 kg	ergo	aircooled	
6	WT330-MED	330 A	60%	1.2 / (1.6)	4.5 mtr	4,1 kg	ergo	aircooled	
7	WT400-SED	400 A	60%	1.2 / (1.6)	3.0 mtr.	3,4 kg	ergo	aircooled	
8	WT400-MED	400 A	60%	1.2 / (1.6)	4.5 mtr	4,6 kg	ergo	aircooled	
9	WTW400-SED	400 A	100%	1.2 / (1.6)	3.0 mtr.	2,7 kg	ergo II	watercooled	
10	WTW400-MED	400 A	100%	1.2 / (1.6)	4.5 mtr	4,0 kg	ergo II	watercooled	
11	WTAW350-SED	350 A	100%	1.2 / (1.6)	3.0 mtr.	2,7 kg	ergo II	watercooled	Aluminium